



Pineline Heavy Duty

Product no.	120
Description	Biosolvent-based presoak concentrate specially for winter conditions.
Special features	Removes tar-residues caused by salted roads. Also dissolves residue from lock lubricants and fuel spills. Can be applied with foam lance. . Does not contain petroleum solvents.
Instructions for use	For use in winter conditions. Typical consumption as a presoak in automatic car wash systems: - as a sill solvent (sill area) 100 – 150 ml (10 – 15%) / passenger car - upper solvent (upper side & roof) 75 – 150 ml (5 – 10%) / passenger car Other uses, e.g. pressure washers: - dilution 5 – 15 % Soaking time 1 min. Rinse with plenty of water.
Note!	Do not let the substance dry on surfaces to be washed. Before using the product, ensure that it is compatible with the material of the washing machine and other surfaces it will come into contact with. FKM/FPM seal is recommended for pump and pressure sprayers. Read the instructions for safe use on the label or in the Safety Data Sheet. Store sealed at +5...+30 °C.
Working environment	Ensure adequate ventilation. The product is easily biodegradable and meets the Ecolabelling requirements.
Technical data	Form and colour clear liquid pH-value (20 °C) 13 pH-value (1 wt-%, 20 °C) 10.8 Relative density 1.01
Content	Nonionic surfactants 15 – 30 %.
Package	10 L, 25 L, 200 L, 1000 L. Empty and rinsed packaging shall be delivered to plastic collection.
Other information	The product has the right to use the Nordic Swan Ecolabel (licence no. 4013-0027). Made in Finland.