



Pineline Asphalt Remover

Product no.	150	
Description	Biosolvent-based extra presoak for cleaning bitumen film and road salt.	
Special features	Also dissolves residue from lock lubricants and fuel spills. Does not contain petroleum solvents. Non-flammable.	
Instructions for use	Pre-dilute the concentrate with cold water. From December-February, dilute at a ratio of 25 – 30 %. During the rest of winter, dilute at a ratio of 15 – 25 %. Mix thoroughly. The concentrate can also be diluted using HydroMinder without a nozzle. In this case, the dilution should be approx. 25 %. In automated car washes equipped with a separate chemical pump and arc, the solution should be sprayed onto the sides and rear of the car. Soaking time 1 min. Rinse with plenty of water.	
Note!	Do not let the substance dry on surfaces to be washed. Before using the product, ensure that it is compatible with the material of the washing machine and other surfaces it will come into contact with. FKM/FPM seal is recommended for pump and pressure sprayers. Read the instructions for safe use on the label or in the Safety Data Sheet. Store sealed at +5...+30 °C.	
Working environment	Ensure adequate ventilation. The product is easily biodegradable and meets the Ecolabelling requirements.	
Technical data	Form and colour pH-value (20 °C) Relative density	clear liquid 9.5 0.96
Content	Nonionic surfactants	> 30 %.
Package	10 L, 25 L, 200 L. Empty and rinsed packaging shall be delivered to plastic collection.	
Other information	The product has the right to use the Nordic Swan Ecolabel (licence no. 4013-0027). Made in Finland.	