## **Pineline**





## **Pineline Comp-clean FA**

Product no. 213

Description Highly alkaline detergent concentrate for washing iron, steel and

aluminium components in mechanical engineering facilities and workshop

maintenance/repair departments. Suitable also for wheel-washing

machines with heating option.

Special features Low-foaming in temperatures over 60 °C. Removes vaseline, burnt-on oil and

grease, and any soot. Protects iron from corrosion.

Instructions for use Make sure that no detergent or dirt residue is left in the washing machine.

Add detergent concentrate to 70-80 °C wash water, concentration 2-5 %. The water temperature must be at least 60 °C before starting the washing machine. Add the product to the washing machine on a regular basis to maintain washing power and to prevent corrosion. For wheel-washing machines, the dilution ratio is 1-5 %. When washing aluminium, check it is

suitable for the product.

Note! Read the instructions for safe use on the label or in the Safety Data Sheet. Store

sealed at +5...+30 °C.

Ecolabel requirements.

Technical data Form and colour clear liquid

pH-value(20 °C) 13.5 pH-value(1 wt-%, 20 °C) 11.9 Relative density 1.15

Contents Non-ionic surfactants 15 – 30 %.

Silicates 10 - 25 %.

Package 25 L, 200 L, 1000 L.

Other information The product has the right to use the Nordic Swan Ecolabel (licence no.

4065-0006). Transportation class: UN 3266. Made in Finland.