



## Pineline Power Cleaner

Product no.	220								
Description	For removing grease, protective compounds and asphalt residue in vehicle servicing and industrial applications. Also suitable as a pre-soak before the car is washed.								
Special features	Also dissolves protective waxes, lock salt and fuel residue, and glue and taping residue. Easy to rinse off. An alternative to raw hydrocarbon solvents.								
Instructions for use	Ready-to-spray solvent. Soaking time 1 min. Rinse with plenty of water, or spray with a pre-wash detergent then rinse thoroughly with water.								
Note!	Do not let the substance dry on surfaces to be washed. FKM seal is recommended for pump and pressure sprayers. Read the instructions for safe use on the label or in the Safety Data Sheet. Store sealed at +5...+30 °C.								
Working environment	Ensure adequate ventilation. The product is easily biodegradable and meets the Ecolabelling requirements.								
Technical data	<table><tr><td>Form and colour</td><td>clear liquid</td></tr><tr><td>pH-value (20 °C)</td><td>6,6</td></tr><tr><td>Relative density</td><td>0,87</td></tr><tr><td>Flash point (ASTM D93)</td><td>&gt; +60 °C</td></tr></table>	Form and colour	clear liquid	pH-value (20 °C)	6,6	Relative density	0,87	Flash point (ASTM D93)	> +60 °C
Form and colour	clear liquid								
pH-value (20 °C)	6,6								
Relative density	0,87								
Flash point (ASTM D93)	> +60 °C								
Package	0,5 L, 25 L, 200 L. Empty and rinsed packaging shall be delivered to plastic collection.								
Other information	The product has the right to use the Nordic Swan Ecolabel (licence no. 4065-0006). Made in Finland.								