

## Pineline Power Cleaner

Product no.	220	
Description	For removal of grease, protective compounds and asphalt residue in vehicle servicing and industrial applications. Suitable also as a pre-soak in automatic car washes.	
Special features	Also dissolves protective waxes, residue from lock lubricants, fuel spills, glue and taping residues. Water-soluble, easy to rinse. Alternative to raw hydrocarbon solvents.	
Instructions for use	Ready-to-use solvent for spraying. Soaking time 1 min. Rinse thoroughly with water, or spray with a pre-wash detergent then rinse thoroughly with water.	
Note!	Do not let the substance dry on surfaces to be washed. Read the instructions for safe use on the label or in the Safety Data Sheet. Recommended to use Viton gasket when applying with pressure applicator. Store sealed at +5...+30 °C.	
Working environment	Ensure adequate ventilation. The product is easily biodegradable and meets Ecolabel requirements.	
Technical data	Form and colour pH-value Relative density Flash point (ASTM D93)	clear liquid 11.4 0.87 >60 °C
Contents	Non-ionic surfactants	15 – 30 %.
Package	0,5 L, 25 L, 200 L.	
Other information	The product has the right to use the Nordic Swan Ecolabel (licence no. 4065-0006). Made in Finland.	

18.10.2018