



## **Pineline**

RODUCT DATA SHEET

16 08 2023

## **Pineline Active Foam**

Product no. 500

Description An alkaline presoak for car wash foam generation equipment (Foam

lance) and pressure washers. Suitable for all types of paint surfaces and

all kinds vehicles for year-round maintenance.

Special features Generates thick, slowly running foam layer. Can also be used as a regular

presoak. Effectively removes traffic film in touchless wash programs and

pressure washing

Instructions for use <u>Dosage as foam in car wash machines:</u>

Typical consumption:

- 10 – 20 ml / passenger car. Soaking time 1 min.

As presoak:

Summer: Dosage < 5 % Winter: Dosage 5 – 15 %.

Soaking time 1 min. Rinse with plenty of water.

Use in Foam lances:

Pour as-is into the foamer bottle and adjust until optimal foam is achieved. The foam is spread onto the surfaces from bottom to top. Soaking time

max. 3 min. Rinse thoroughly with water.

Note! Do not let the substance dry on surfaces to be washed. Avoid using the

product in direct sunlight Before using the product, ensure that it is

compatible with the material of the washing machine and other surfaces it will come into contact with. Read the instructions for safe use on the label

or in the Safety Data Sheet. Store sealed at +5...+30 °C.

Working environment Ensure adequate ventilation. The product is easily biodegradable and

meets the Ecolabelling requirements.

Technical data Form and colour yellowish liquid

pH-value (20 °C) 12,9 pH-value (1 wt-%, 20 °C) 11,7 Relative density 1.09

Content Nonionic surfactants 5 - 15 %.

Package 4 L, 10 L, 25 L, 200 L, 1000 L.

Empty and rinsed packaging shall be delivered to plastic collection.

Other information The product has the right to use the Nordic Swan Ecolabel (licence no.

4013-0027). Made in Finland.