Pineline Fusion Ceramic Essence

Art.nr.	860
Description	Ceramic WetCoat spray sealant developed for wash tunnels and Roll-over machines to protect the car's exterior, glass and metal surfaces.
Special features	The SiO2 structure of the product offers long-lasting protection and repellency against dirt. The coating retains its properties even after several washes. Thanks to its excellent hydrophobicity and slickness, dirt is easily washed off from surfaces. The gloss also deepens.
Instructions for use	The product is dosed immediately after the washing step in clean rinsing water on wet surfaces. Recommended consumption: - 40 – 80 ml / passenger car Advanced concentration: 1 – 2 %. A separate freshwater rinse is recommended before air blowing.
Note!	Read the instructions for safe use on the label or Safety Data Sheet. Store sealed at +5…+ 30 ºC.
Working environment	Provide adequate ventilation.

Technical data	Form and colour	pink liquid
	pH-value (20 ºC)	5
	Relative density	1
Content	Polyorganic siloxanes	5 – 15 %

Package	10 L, 25 L. Empty and rinsed packaging shall be delivered to plastic collection.
Other	Made in Finland.

© TEKNO-FOREST OY • 1000117-0 • Kynttilätie 3, 11710 Riihimäki, FINLAND
www.pineline.com • +358 19 774 860 • info@pineline.com
CERTIFIED
ISO 9001
ISO 14001