

APPLICATION TABLE – PINELINE PRODUCTS FOR USE IN INDUSTRIAL PARTS CLEANING MACHINES

04.07.2024

COMP-CLEAN 35 – COMP-CLEAN FA – COMP-CLEAN LT – PARTS CLEAN – METALLIC CLEANER

Object of use

-Pre-wash for assembly painting and final processing in the metal and workshops	**	*	*	**	*
- For washing engine, machine and other heavily soiled parts	**	**	-	-	**
-Low-foaming detergent for tire washing machines in tire shops and repair shops	-	**	**	-	-
- Parts detergent for washing aluminum and yellow metals	-	* _{Al}	-	**	* _{Al}

Operating area

Maintenance / Repair shops	*	**	*	-	**
Industry / Work shops	**	*	*	**	**
Industrial washing machines	**	**	**	**	-
Ultrasonic washing machines	-	-	-	*	**

Soil type


Machining residues and metal scrap	**	*	**	**	*
Burnt grease and soot	**	**	*	*	**

pH-value (undiluted)

1 % dilution	13,1	13,2	13,5	10,2	13,3
--------------	------	------	------	------	------

Applicability

Iron metals	**	**	**	**	**
Aluminium	-	*	-	**	-



Brass/Copper

-

-

-

**

-

Corrosion protection

**

*

*

*

*

Operating temperature

+60...+80 °C

**

**

**

**

**

+5...+80 °C

-

-

**

-

**

** well applicable

* moderately applicable

- not applicable

SOVELLUSTAULUKKO – PINELINE OSIENPESUAINEET

04.07.2024

COMP-CLEAN 35 – COMP-CLEAN FA – COMP-CLEAN LT – PARTS CLEAN – METALLIC CLEANER

Käyttökohde

-Metalli- ja konepajateollisuuden kokoonpanoa edeltävät pesut	**	*	*	**	*
-Moottori-, kone- ja muiden vaikeasti likaantuneiden kappaleiden pesuun	**	**	-	-	**
-Matalavaahtoinen pesuaine rengasliikkeiden ja korjaamoiden rengaspesukoneisiin	-	**	**	-	-
-Osienpesuaine alumiinin ja keltametallien pesuun	-	* Al	-	**	* Al

Käyttöalue

Kunnossapito / Korjaamot	*	**	*	-	**
Teollisuus / Konepajat	**	*	*	**	**
Kammiopesukoneet	**	**	**	**	-
Ultraäänipesukoneet	-	-	-	*	**

Likatyyppi

Työstöjäämät, metallikarsta	**	*	**	**	*
Kiinnipalanut rasva ja noki	**	**	*	*	**

pH-tiiviste	13,1	13,2	13,5	10,2	13,6
1 % käyttöliuos	12,1	11,9	11,2	9,8	11,6

Soveltuvuus

Rautametallit	**	**	**	**	**
Alumiini	-	*	-	**	-
Messinki/kupari	-	-	-	**	-
Korroosiosuoja	**	*	*	*	*

Käyttölämpötila

+60...+80 °C

+5...+80 °C

■

■

** soveltuu hyvin

* soveltuu kohtalaisesti

- ei sovellu